TOMCAT®

Imported from Racine, WI - USA

Premium Walk-Behind Scrubbers v2 Series

Sport | Carbon | Hero



*Images could include non-standard options. Subject to change without notice.

Family-Owned & Operated



Stand-On



Walk-Behind Scrubbers



Ride-On Scrubbers



Sweepers

Choose Your Chassis



Sport Specs

- Up to 52,000 sqft/Charge
- 13 / 15 Gallons
- 20 - 28 inch decks

Applications

- Automotive Shops
- Machine Shops
- Warehouses



Carbon Specs

- Up to 102,000 sqft/Charge
- 21 / 23 Gallons
- 24 - 29 inch decks

Applications

- Fabrication Shops
- Beverage Distribution
- Food Packaging



Hero Specs

- Up to 170,000 sqft/Charge
- 30 / 32 Gallons
- 28 - 34 inch decks

Applications


- Distribution
- Sports Arenas
- Aviation

Choose Your Scrub Deck




Cylindrical Benefits

- Eliminates Pre-Sweeping
- Scrub & Sweep Simultaneously
- Superior Tile & Grout Cleaning
- Great for Indoor Track Fields



Disk Benefits

- Largest Brush/ Pad Selection
- Lowest Maintenance Cost
- Best Performance on Irregular Floors
- Brushes Individually driven



EDGE Benefits

- Chemical Free Stripping
- Reduce Slip & Fall Potential
- 70% Reduction in Water Usage
- VCT Prep & Recoat

Choose Your Controller

3″ color LCD with membrane controls
Standard



Membrane with Plain LCD
Optional




4″ color touchscreen
Optional



www.tomcatequip.com 262-681-6470 RPS Corporation, 1711 South St, Racine, WI, 53404, USA

Choose Your Chassis



1* Polypropylene: Black / Medium - Light

2 Nylon: White / Light - Soft

3 Tampico: Tan / Soft

4* Tufted Pad Driver: Red / Variety Pads

5* SNAP Diamond Driver: Black / Variety Diamond Pucks

6* Super Grit: Orange / Extreme Rough


7 Tough Grit: Black / Very Rough

8 Midi Grit: Blue / Rough

9 Light Grit: Grey / Medium


*Not offered on cylindrical brushes

Brush availability varies by size and deck type.



www.tomcatequip.com 262-681-6470 RPS Corporation, 1711 South St, Racine, WI, 53404, USA

View Inside



*Images could include non-standard options. Subject to change without notice.

www.tomcatequip.com 262-681-6470 RPS Corporation, 1711 South St, Racine, WI, 53404, USA

Choose Your Options




Antimicrobial Sanitation Package

- Clean With Chemical or Aqueous Ozone
- Spray Wand For Hard To Reach Places
- Antimicrobial Tank
- Dedicated 3 Gallon Disinfectant Tank



Scrub And Vac Wand / Spray Jet

- Brush for scrubbing, squeegee for water pickup
- Clean restrooms and under tables
- Pre-soak the floor before scrubbing
- Rinse out recovery tank



WET / AGM / Lithium Batteries

- Choose from wet lead-acid, maintenance-free AGM, or lithium-ion batteries to match your cleaning needs.



Stainless Frame

- Stainless Metal prolongs machine life
- Helps resist corrosion from moisture/chemical
- Great for corrosive applications (fertilizer, salt spreading for DOT)



Suds / ZERO3

- Automatic chemical dilution with Suds
- Cleaning with chemical free Aqueous Ozone



Metal Lid / HD Wheels / Jaws

- Metal Recovery Lid
- Metal-Hub Drive Tires
- Heavy Duty Jaws

Easy Access to key components:

- Vac Motor
- Batteries
- Deck Actuator
- Solution Valve
- Filters-Screens
- Soap Drain
- Battery Box Drain
- Unloader Valve
- Vac Switch
- Scrub Motors



Tip Back Tank

Our designers all have 25+ years of experience and recognize cleaning equipment will eventually require service.

- Tanks tip back without tools, providing easy top side access to all important service items.

- Quick access allows the technician to troubleshoot while standing and make repairs quickly, with less chance of creating unintended problems from disassembling 5 items to get to the 1 that failed.




Large Clear Lid

Any customer who has previously owned and operated cleaning equipment will appreciate the value of full time viewing of the dirty water recovery tank.

- This provides the operator with a real time view of the dirty water level, foam, debris tray, the vacuum's white dust filter and more.

- The fully accessible recovery tank is easily our most significant feature for cost reduction. Open the lid to clean out the recovery tank, eliminating odors and other contaminants which can become airborne and inhaled by employees.



Steel Frame

We spend the extra time and money to through-bolt with stainless fasteners for longevity and service ease in the future. Some of our larger machines have 600-lbs in batteries in a full height poly liner, supported by the steel frame.

• All assemblies mount directly to the 7-ga (3/16" thick) steel frame, instead of plastic parts that will fatigue in time.

• Accidental damage to casters, or over tensioning the frame during transport will not damage our tanks since we don't bolt collision points to the poly tank.




Baffle System

Another feature you'll not find elsewhere is our stainless baffle wall that controls foam in the recovery tank.

• The dirty water passes into our drain saver basket, and then fills up the rear side of the baffle such that the foam doesn't migrate to the front where the stainless screen and ball float operate.


• The stainless screen and white vacuum filter offer additional protection. These are the first of several steps taken to ensure good airflow (squeegee performance) to protect the vacuum motor from moisture.

You Be The Judge




Patented Bandeau System

- This design was so unique and meaningful it earned a US Patent, and something you won't find elsewhere.
- The black bandeau is vacuumized and holds 1-gallon of foam or dirty water away from the vac motor, backing up the primary filters and balls screens.
- The "unloader" valve automatically drains off any residual water when vac is OFF.
- The yellow muffler box both reduces the noise and also directs any digested water out a tube, to alert the operator to a problem.



Steel Squeegee

- Locking latches front and rear
- Range of material for different applications
- Smooth and Rough floor hole patterns





Education

Schools frequently value the maneuverability of our designs for those congested areas and small elevators. Both K though 12 and universities utilize the superior productivity from our large tank capacities and run time. Onboard ozone (ZERO3) and our EDGE Orbital technology greatly reduce the use of chemicals and afford meaningful cost savings.



Healthcare

Low noise and optimized water control are key features our healthcare customers require. Our patented vacuum protection and muffler system allow for high performance motors to operate at unmatched levels. These scrubbers combine heavy duty cleaning and drying with noise levels suitable for facilities that operate around the clock.



Sports Arena

Our products are used extensively on wood, vct, rubber running tracks, concrete, artificial turf and other surfaces that are unique to athletics departments. The wide range of scrub head types and sizes, combined with the assortment of brushes and pads allow for the greatest flexibility.

Applications



Hotels - Hospitality

Food and guests services require a high level of cleaning and frequency. Equipment that can cut through heavy grease, navigate commercial kitchens and public lobbies alike. Hotel and resort casinos understand the cleaning equipment must be available to operate 24/7 and often perform housecleaning role in close proximity to customers.



Retail - Grocery

Many in this category are moving away from the cheap imported products to our American made equipment that affords them better cleaning performance and less downtime for repairs. Shopping malls, large retail box stores and grocery stores have high daily traffic and often need to clean up product spills promptly in the presence of customers. A quiet and quality cleaning machine sends a good message to the clients that the organization values sanitation.



Distribution - Warehouse

Our company “industrial equipment” origins result in the most durable equipment offered to the “commercial” sector. Warehouse and distribution centers utilize powerful material handling equipment and steel racking. The cleaning equipment needs to be built to pick up heavy soil, broken pallets, nails and also survive the inevitable collisions with fork trucks and racking.

Specifications



Sport v2 Series

BODY CONSTRUCTION / DIMENSIONS	
Chassis Construction:	3/16" Steel *(4.8 mm)* Powder Coated
Front Wheels (Ø × Width)	(2×) 8" × 2" *([2×] 20 × 5 cm)* - Non-Marking Grey
Rear Casters (Ø × Width):	(2×) 2.5" × 1.38" *([2×] 6 × 4 cm)* - Black
Size (L × W × H): *Smallest machine configuration.	50" × 23" × 39" *(127 × 59 × 99 cm)*
Weight (w/o Batteries):	278 - 328 lbs *(126 - 149 kg)*
Weight (with Batteries):	410 - 460 lbs *(186 - 209 kg)*
BRUSH / PAD SYSTEM	
Disk Dimensions:	20" - (1×) 20" Ø *(51 - [1×] 51 cm)* 26" - (2×) 13" Ø *(66 - [2×] 33 cm)*
Disk Motor:	20" (1×) 0.75 hp/ 200 rpm *(51 cm [1×] 559 watts)* 26" - (2×) 0.75 hp/ 270 rpm *(66 cm [2×] 559 watts)*
Optional Motor Upgrade:	20" only - (1×) 1.0 hp / 350 rpm *(746 watts)*
Cylindrical Dimensions: 6" Ø Brush	25" - (2×) 6" × 23" *(64 - [2×] 15.2 × 58 cm)*
Cylindrical Motor:	(2×) 0.75 hp *([2×] 559 watts)*
Cylindrical Brush Speed:	750 rpm
EDGE Dimensions:	20" × 14" *(51 × 35.6 cm)* 24" × 14" *(61 × 35.6 cm)* 28" × 14" *(71 × 35.6 cm)*
EDGE Motor:	1.0 hp *(746 watts)* 2,500 rpm
Optional Motor Upgrade:	(1×) 1.2 hp / 2,900 rpm *(895 watts)*
Brush Down Pressure:	Up to 175 lbs *(79 kg)* / 500 lbs *(227 kg)* Actuator Rating
POWER SYSTEM	
System Voltage/Amps	24 VDC / 130 Ah WET
Optional Battery:	150 Ah WET / 150 Ah AGM 90 Ah Li-ion
Run Time: **Based on continuous scrubbing run times.	Up to 2.5 Hours**
DRIVE SYSTEM	
Power:	0.75hp - All Gear / Sealed *(559 watts)*
Forward Speed:	0 - 230 ft/min / 0 - 2.6 mph *(0 - 70 m/min / 0 - 4 km/h)*
Scrubbing Speed:	0 - 184 ft/min / 0 - 2 mph *(0 - 56 m/min / 0 - 3 km/h)*
Reverse Speed:	0 - 130 ft/min / 0 - 1.5 mph *(0 - 40 m/min / 0 - 2 km/h)*
SOLUTION / RECOVERY SYSTEMS	
Solution Tank Capacity:	13 Gallons *(49 liters)* - w/ Graduated Sight Tube
Solution Flow / Filter:	0 - 0.5 GPM / Stainless Inline *(0 - 2 LPM)*
Recovery Tank Capacity:	15 Gallons *(56.8 liters)* - 1.5" Ø Drain Hose
Optional Tank:	N/A
Demisting Chamber:	1.25 Gallons *(4.7 liters)*
Drain Saver:	30 cubic inches *(492 cubic cm)*
Vacuum Power (Water Lift / Airflow):	0.8 hp / 3 Stage / 5.7" Ø *(597 watts)* 68" / 72 cfm *(173 cm / 2 m³/min)*
GENERAL	
Productivity - Theoretical: ***Based off of ISSA 2010 Cleaning Times	Up to 26,000 sqft/hr *(2,415 m²/hr)****
Productivity - Practical: ***Based off of ISSA 2010 Cleaning Times	Up to 12,059 sqft/hr *(1,120 m²/hr)****



Carbon v2 Series

BODY CONSTRUCTION / DIMENSIONS	
Chassis Construction:	3/16" Steel *(4.8 mm)* Powder Coated
Front Wheels (Ø × Width)	(2×) 10" × 2.5" *([2×] 25.4 × 6 cm)* - Non-Marking Grey
Rear Casters (Ø × Width):	(2×) 4" × 2" *([2×] 10 × 5 cm)* - Black
Size (L × W × H): *Smallest machine configuration.	56" × 28" × 43" *(142 × 71 × 109 cm)*
Weight (w/o Batteries):	393 - 443 lbs *(178 - 201 kg)*
Weight (with Batteries):	625 - 675 lbs *(284 - 306 kg)*
BRUSH / PAD SYSTEM	
Disk Dimensions:	26" - (2×) 13" Ø *(66 - [2×] 33 cm)* 28" - (2×) 14" Ø *(71 - [2×] 35 cm)*
Disk Motor:	(2×) 0.75 hp / 270 rpm *([2×] 559 watts)*
Optional Motor Upgrade:	1.0 hp / 340 rpm *(746 watts)*
Cylindrical Dimensions: 6" Ø Brush	25" - (2×) 6" × 23" *(63 - [2×] 15 × 58 cm)* 29" - (2×) 6" × 27" *(73 - [2×] 15 × 68 cm)*
Cylindrical Motor:	25" - (2×) 0.75 hp *([2×] 559 watts)* 29" - (2×) 1.0 hp *([2×] 746 watts)*
Cylindrical Brush Speed:	750 rpm
EDGE Dimensions:	24" × 14" *(61 × 35 cm)* 28" × 14" *(71 × 35 cm)*
EDGE Motor:	1.0 hp *(746 watts)* 2,500 rpm
Optional Motor Upgrade:	(1×) 1.2 hp / 2,900 rpm *(895 watts)*
Brush Down Pressure:	Up to 175 lbs *(79 kg)* / 500 lbs *(227 kg)* Actuator Rating
POWER SYSTEM	
System Voltage/Amps	24 VDC / 210 Ah WET
Optional Battery:	240 Ah WET / 224 Ah AGM 180 Ah Li-ion
Run Time: **Based on continuous scrubbing run times.	Up to 3.5 Hours**
DRIVE SYSTEM	
Power:	0.75hp - All Gear / Sealed *(559 watts)*
Forward Speed:	0 - 290 ft/min / 0 - 3.3 mph *(0 - 88 m/min / 0 - 5 km/h)*
Scrubbing Speed:	0 - 229 ft/min / 0 - 2.6 mph *(0 - 70 m/min / 0 - 4 km/h)*
Reverse Speed:	0 - 202 ft/min / 0 - 2.3 mph *(0 - 61 m/min / 0 - 4 km/h)*
SOLUTION / RECOVERY SYSTEMS	
Solution Tank Capacity:	21 Gallons *(79 liters)* - w/ Graduated Sight Tube
Solution Flow / Filter:	0 - 0.7 GPM / Stainless Inline *(0 - 2.65 LPM)*
Recovery Tank Capacity:	23 Gallons *(87 liters)* - 1.5" Ø Drain Hose
Optional Tank:	N/A
Demisting Chamber:	1.25 Gallons *(4.7 liters)*
Drain Saver:	30 cubic inches *(492 cubic cm)*
Vacuum Power (Water Lift / Airflow):	0.8 hp / 3 Stage / 5.7" *(597 watts)* 68" / 72 cfm *(173 cm / 2 m³/min)*
GENERAL	
Productivity - Theoretical: ***Based off of ISSA 2010 Cleaning Times	Up to 29,029 sqft/hr *(2,696 m²/hr)****
Productivity - Practical: ***Based off of ISSA 2010 Cleaning Times	Up to 13,454 sqft /hr *(1,250 m²/hr)****



Hero v2 Series

BODY CONSTRUCTION / DIMENSIONS	
Chassis Construction:	3/16" Steel *(4.8 mm)* Powder Coated
Front Wheels (Ø × Width):	(2×) 12" × 2.75" *([2×] 30 × 7 cm)* - Non-Marking Grey
Rear Casters (Ø × Width):	(2×) 5" × 2" *([2×] 12.7 × 5.1 cm)* - Black
Size (L × W × H): *Smallest machine configuration.	62" × 31" × 43" *(157 × 79 × 109 cm)*
Weight (w/o Batteries):	441 - 481 lbs *(200 - 218 kg)*
Weight (with Batteries):	775 - 825 lbs *(352 - 374 kg)*
BRUSH / PAD SYSTEM	
Disk Dimensions:	30" - (2×) 15" Ø *(76 - [2×] 38 cm)* 32" - (2×) 16" Ø *(82 - [2×] 41 cm)* 34" - (2×) 17" Ø *(86 - [2×] 43 cm)*
Disk Motor:	(2×) 1.0 hp / 350 rpm *([2×] 746 watts)*
Optional Motor Upgrade:	NA
Cylindrical Dimensions: 6" Ø Brush	29" - (2×) 6" × 27" *(73 - [2×] 15 × 68 cm)* 33" - (2×) 6" × 31" *(83 - [2×] 15 × 78 cm)*
Cylindrical Motor:	(2×) 1.0 hp *([2×] 746 watts)*
Cylindrical Brush Speed:	750 rpm
EDGE Dimensions:	28" × 14" *(71 × 35 cm)* 32" × 14" *(81 × 35 cm)*
EDGE Motor:	1.0 hp *(746 watts)* 2,500 rpm
Optional Motor Upgrade:	(1×) 1.2 hp / 2,900 rpm *(895 watts)*
Brush Down Pressure:	Up to 185 lbs *(84 kg)* / 500 lbs *(227 kg)* Actuator Rating
POWER SYSTEM	
System Voltage/Amps	24 VDC / 310 Ah WET
Optional Battery:	360 Ah WET / 335 Ah AGM 180 Ah Li-ion
Run Time: **Based on continuous scrubbing run times.	Up to 5.0 Hours**
DRIVE SYSTEM	
Power:	0.75hp - All Gear / Sealed *(559 watts)*
Forward Speed:	0 - 290 ft/min / 0 - 3.3 mph *(0 - 88 m/min / 0 - 5 km/h)*
Scrubbing Speed:	0 - 229 ft/min / 0 - 2.6 mph *(0 - 70 m/min / 0 - 4 km/h)*
Reverse Speed:	0 - 202 ft/min / 0 - 2.3 mph *(0 - 61 m/min / 0 - 4 km/h)*
SOLUTION / RECOVERY SYSTEMS	
Solution Tank Capacity:	30 Gallons *(113 liters)* - w/ Graduated Sight Tube
Solution Flow / Filter:	0 - 1.0 GPM / Stainless Inline *(0 - 4 LPM)*
Recovery Tank Capacity:	32 Gallons *(121 liters)* - 1.5" Ø Drain Hose
Optional XL tank:	35 Gal *(132 liters)* Solution 37 Gal *(140 liters)* Recovery
Demisting Chamber:	1.25 Gallons *(4.7 liters)*
Drain Saver:	30 cubic inches *(492 cubic cm)*
Vacuum Power (Water Lift / Airflow):	0.8 hp / 3 Stage / 5.7" *(597 watts)* 68" / 72 cfm *(173 cm / 2 m³/min)*
GENERAL	
Productivity - Theoretical: ***Based off of ISSA 2010 Cleaning Times	Up to 33,932 sqft/hr *(3,152 m²/hr)****
Productivity - Practical: ***Based off of ISSA 2010 Cleaning Times	Up to 15,784 sqft /hr *(1,466 m²/hr)****

Our Family's American Dream

Authorized Distributor

RPS **has been family owned from it's inception in 1986, and proudly builds in Wisconsin (USA). The company has grown over the last 40-years with a strong group of executives including the 2nd generation of family owners who started in the shop as youngsters.**



Assembled By Hand

Our American workforce hand builds each machine with components heavily sourced from American suppliers. We routinely pay more for these domestically supplied components required to build a superior product. All design, prototyping, production and testing is done in-house where we can best control quality.



Steel Fabrication

We produce heavy duty equipment and require a good amount of thick steel in the construction. We use a combination of Stainless 304 (Austenitic 18/8) and mild steel with e-coating + powder paint for corrosion resistance. Steel fabrication is done in-house or from local suppliers with specialty equipment.



Rotational Molding

Complex shapes that allow for our "tank-in-tank" design are best achieved with in-house equipment. We own multiple dual station rotational molding machines that allow us to produce finished parts from raw plastic. Producing consistently higher quality parts, and respond quickly to sales spikes.



Product Design

Our team has designed and engineered over 100 unique machines. Each new generation of machines evolve from prior designs to retain the strengths and correct any weakness. From the first pencil sketch we focus on durability, serviceability, performance, productivity, specifications, and value.

V26.281